

Screenplay

Network/Curtain Call/Partition/Frames

SPECIFICATION	
Construction	Tufted Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50cmX50cm
Dye Method	Solution Dyed
Gauge	1/12
Stitches	9.1
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	41.9% (38.2% Post Industrial, 3.7% Post Consumer)
Nominal Total Thickness	5.5mm±10%

PERFORMANCE		WARRANTIES
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)	Lifetime Face Fiber Wear
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450	Lifetime Antistatic
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing	Lifetime Floor Compatibility
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours	Lifetime Color Pattern Permanency
Crocking (AATCC 165)	≥ 4.0 Wet or Dry	Lifetime Floor Release
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber	Lifetime Moisture Resistance
Texture Appearance Retention Rating (TARR)	Heavy	Lifetime Delamination of Backing
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X	Lifetime Dimensional Stability
		Lifetime Tuft Bind
		Lifetime Edge Ravel
		Lifetime Flammability

INSTALLATION METHOD



Monolithic

3RD PARTY CERTIFICATES



Declare.



Design Copyright – Milliken & Company. This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com

© 2025 Milliken & Company | Made in China