

PRODUCT Answer Beam

STYLE NUMBER TSB24TK, TSB24HS, TSB24HSBOB, TSB24HSF, TSB24LS, TSB24WS, TSBUWCM, TSBRF, TSBSCSSD, TSBBOBTRM, TSB28LVT, TSBTJC, TSB424CTCHT, TSBBST, TSBUB2PK6048, TSBTB1, TSBFC24RH, TSBFQ24RH, TSBFH24RHB, TSB1610H, USWSVB, BSVB1, BSMC, TSBERUP, TSB28TUP, TSBAWAK, TSB15H, TSBSTS, TSBUCANT, TSB24HF, TSB24TC, TSB28TJ, TSB424CTJ, TSB28JP

PRODUCT OPTIONS BEAM SKIN - TACKABLE ACCOUSTICAL, 24W, BEAM SKIN - HARD SURFACE, 24W, BEAM SKIN - HARD SURFACE, 24W, BIG OPEN, BEAM SKIN -HARD SURFACE, 24W, FLOOR, BEAM SKIN - LAMINATE, 24W, BEAM SKIN - WOOD, 24W, UNDER WORKSURFACE CABLE MANAGER - BEAM F, ANSWER SKIN RECEPTACLE FILLER, PKG OF 2, SCREEN - SINGLE SIDED, SINGLE CONNECT, S, BEAM BIG OPEN BASE TRIM PKG, BEAM TRIM – VERTICAL L, 28.5, BEAM JUNCTION CAP – T, BEAM TRIM - T COH, 42/28/42, BOUNDARY SCREEN - ON MODULAR T, STORAGE TO BEAM CONNECTOR LH- 1H FOR USE, STORAGE TO BEAM CONNECTOR LH RECESSED BA, STORAGE TO BEAM CONNECTOR LH- 1H FOR USE, STORAGE TO BEAM CONNECTOR LH RECESSED BA, BENCH, BEAM APPLICATION, QTY2, LAMINATE, TETHER BRACKET – SINGLE, LEG- UNIVERSAL, RIGHT HAND, CLOSED LOOP, LEG- UNIVERSAL, RIGHT HAND, OPEN LOOP, B, LEG- UNIVERSAL, RIGHT HAND, HALF, BEAM S, INTERMEDIATE WORKSURFACE SUPPORT - 1H, VERB BRACKET FOR UNIVERSAL WORKSURFACES, VERB BRACKET FOR BOUNDARY SCREEN-SINGLE, VERB BRACKET MARKER CLIP (PKG OF 20), UTILITY POLE EOR, BEAM HEIGHT T JUNCTION UTILITY POLE, GANGING KIT FOR CONNECTING STORAGE UNITS, MID STORAGE SUPPORT- 1.5H, STANCHION KIT - SINGLE SIDED, UNIVERSAL CANTILEVER - BEAM APPLICATION, BEAM FRAME PKG - HORIZONTAL, 24W, BEAM TOP CAP RAIL - 24W, BEAM JUNCTION – T, BEAM JUNCTION - T, COH, 42/28/42, BEAM JUNCTION POST - 28.5H

EXCEPTIONS RL-004a – Proprietary Ingredients, RL-009 – Formaldehyde

FINAL ASSEMBLY LOCATION Steelcase Athens

BIFMA LEVEL CERTIFIED Level 3

INDOOR AIR QUALITY SCS Indoor Advantage Gold

RED LIST LBC Red List v4.0, BIFMA a3-2019 Annex B

DATE 05/26/2023

NOTE: Excluding electrical/electronic components

INGREDIENTS See next page

INGREDIENTS	CAS RN	% Weight
carbon steel	12597-69-2	60.56
ligno-cellulosic materials (wood)	-	22.21
extruded aluminum alloy 6063	6063	10.03
melamine-urea-formaldehyde polymer	25036-13-9	2.08
urea, polymer with formaldehyde	9011-05-6	0.74
phenol formaldehyde polymer	9003-35-4	0.74
proprietary ingredients	-	0.54
poly(Bisphenol A-co-epichlorohydrin) glycidyl	25036-25-3	0.46
melamine formaldehyde polymer	9003-08-1	0.28
nylon-6	25038-54-4	0.27
saturated polyester resin	61926-16-7	0.23
polypropylene	9003-07-0	0.22
ammonium sulfate	7783-20-2	0.22
polyvinyl acetate	9003-20-7	0.22
slack wax (petroleum)	64742-61-6	0.19
glass, oxide, chemicals	65997-17-3	0.17
urea	57-13-6	0.18
water	7732-18-5	0.12
poly(vinyl acetate)	9003-20-7	0.07
ammonium chloride	12125-02-9	0.06
2-oxohexamethylenimine	105-60-2	0.06
cast aluminum alloy ADC12	ADC12	0.05
slack wax, petroleum	64742-61-6	0.05
amorphous precipitated silica	112926-00-8	0.05
1,3,5-trioxane, polymer with 1,3-dioxolane	24969-26-4	0.04
zinc	7440-66-6	0.02
titanium(IV) oxide, rutile	1317-80-2	0.02
aluminum oxide	1344-28-1	0.02
acrylonitrile-butadiene-styrene	9003-56-9	0.01
starch	9005-25-8	0.01
polystyrene-block-polyisoprene-block-polystyrene	25038-32-5	0.01
Grand Total		100

* The table above contains materials chemistry information by CAS number for the product listed above. Steelcase does not own the formulation chemistry for any of the materials in its products. Steelcase (and our affiliates/agents) strives to collect chemistry information from suppliers down to 100 ppm per homogeneous material. Because this level of chemistry is not always available, it is not possible to say with certainty that products are completely free of any given chemical. Internal expertise is used to make judgements about the presence or absence of certain chemicals as intentionally added ingredients. Users should be aware that the information available may represent a typical product representation and may not reflect the exact product being specified.